



WODC OIL DEGREASER

DESCRIPTION

WODC OIL DEGREASER is a solvent based, water miscible oil, grease and fat degreaser for concrete and cement substrates.

PURPOSE

To degrease oil, grease and fat stained concrete floors.

APPLICATION

Pour the WODC OIL DEGREASER evenly over the floor in the area to be degreased.

Spread the degreaser with a stiff broom at a rate of about 500ml to 1L per m² (depending on the degree of oil or grease contamination) and scrub the degreaser in, using a stiff broom. Leave the degreaser on the floor for about 10 to 15 minutes.

Pour water over the floor and scrub again, using the stiff broom. The mixture will become milky. Leave for another 10 to 15 minutes and rinse everything off with water.

Let the floor dry thoroughly before preparation and primer coats.

A second procedure can be followed if there is still a substantial amount of oil or grease left in the concrete.

It is not possible to completely remove oil or grease stains from concrete.

PHYSICAL PROPERTIES:

Colour: water white
Specific gravity: 0,86g/cc
Coverage: 500ml/m²

PACKAGING:

WODC OIL DEGREASER is supplied in 5lt and 25lt screw cap, plastic containers.

PRECAUTIONS

Apply in a well ventilated room. Clean tools with water immediately after use.

Do not ingest. Keep away from children and pets. Do not empty into drains.

Wear rubber gloves. In the event of contact with eyes or skin, rinse thoroughly with cold water. If irritation or discomfort occurs, seek medical advice.

Do NOT allow oil degreaser into storm water drains or other water drainage systems.

MANUFACTURED BY

Stucco Italiano
25 Industria Rd, Brackenfell
Tel: 021- 982 0006
E-mail: info@stuccoitaliano.co.za
www.wodc.co.za



World of
Decorative Concrete