



WODC POLISHED CONCRETE SEALER

DESCRIPTION

WODC Polished Concrete Sealer is a single phase, clear solvent sealer for polished concrete surfaces. It is a transparent, water white liquid with a distinctive smell.

PURPOSE

WODC Polished Concrete Sealer is applied to ground and polished concrete surfaces, penetrates and seals it off. It enhances the colour of the concrete and improves the shine during the burnishing process.

APPLICATION

After the last polishing phase, the following steps are followed:

- 1) Vacuum clean the floor
- 2) Wash and clean using burnisher
- 3) Vacuum clean
- 4) Apply WODC Polished Concrete Sealer with roller and brush and allow to dry for 24 hours
- 5) Burnish

TECHNICAL DATA

Type:	Solvent based
Touch Drying time:	4 to 6 hours @ 23°C
Shelf life:	12 months
Coverage:	± 15m ² per litre
Packaging:	1L, 5L and 25L quantities.
Storage:	Store in a cool dry place away from heat and open flames.

WARNING

WODC Polished Concrete Sealer is flammable.
Do not ingest. Keep away from children and pets. Do not empty into drains.

PRECAUTIONS

Wear rubber gloves. In the event of contact with eyes or skin, rinse thoroughly with cold water.
If irritation or discomfort occurs, seek medical advice.

MANUFACTURED BY

Stucco Italiano
25 Industria Rd, Brackenfell
Tel: 021- 982 0006
E-mail: info@stuccoitaliano.co.za
www.wodc.co.za